Electronic Frequency Converter









DESIGNED FOR YOUR NEEDS



OPTIMUM PERFORMANCE



HIGH PRODUCTIVITY



ELECTRONIC FREQUENCY CONVERTER

for precast plants and contruction sites





DESIGN	MODEL	N° OUTLETS	INPUT			OUTPUT		
			VOLTAGE (V)	FREQUENCY (Hz)	CURRENT (A)	POWER (KW)	VOLTAGE (V)	CURRENT (A)
MOBILE	EC 400/4 M	4	380/500	50/60	27	7,5	400	17
	EC 230/4 M						230	30
	EC 42/4 M		380/440		25	7	42	100
	EC 400/8 M	8	380/500	50/60	48	15	400	33
	EC 230/8 M						230	57
	EC 42/8 M						42	314
FIX	FULLY CUSTOMIZED SOLUTION. DESIGNED ACCORDING TO SPECIFICATION.							



DESIGNED FOR YOUR NEEDS

Available in 2 different designs: mobile or fix.

MOBILE → Power from 4 up to 8 vibrators simultaneously.

Flexible solution, suitable both for construction sites and precast plants.

FIX → Suitable to power multiple vibrators at the same time. Fully customized according to customer reguest.



OPTIMUM PERFORMANCE

Input voltage: 380/500V ±10%, 50/60Hz.

Output voltage: available in 400V, 230V or 42V.

Output frequency: adjustable through potentiometer.

Full protection against: overload, short circuit, over temperature and voltage fluctuation.



HIGH PRODUCTIVITY

Possibility to power on the vibrators one by one, in groups or all together.

Maintenance free thanks to high quality components.

WHEN YOU NEED IT, WHERE YOU NEED IT.

WWW OLIVIBRA COM

